

## Akumulacioni tankovi BT od nerđajućeg čelika

Model		BT100TC-1	BT100TC-2	BT200TC	BT200TC-1
Max. water pressure	bar	10	10	10	10
Max. water temperature	°C	95	95	95	95
Volume	l	100	100	200	200
Hight	mm	1500	1500	1500	1500
Diameter	mm	375	375	520	520
Material of inner tank	/	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304
Material of coil	/	Stainless steel 316	Stainless steel 316	/	Stainless steel 316
Insolation - Type / Thickness	mm	Polyurethan / 37,5	Polyurethan / 37,5	Polyurethan / 50	Polyurethan / 50
Color	/	White	White	White	White
Thermometer	/	Yes	Yes	Yes	Yes
Weight	kg	26,2	29,3	41,2	46,3
Coil	m	/	15	/	20
2 inch/ R50 connector	pcs	/	1	1	1
Wall bracket	/	Yes	Yes	/	/
Connections	/	On top	On top	On top	On top
Temperature sensor pocket	pcs	2	2	2	2

## Multifunkcionalni tankovi od nerđajućeg čelika

Model		MWT 300.4-3H	MWT 500.4-3H
Water pressure Max.	bar	10	10
Water temperature Max.	°C	95	95
Volume	l	300	500
Height	mm	1560	1850 (rising height 2000)
Diameter	mm	630	708
Inner tank and coils		Stainless 304 and 316	Stainless 304 and 316
Outer tank		Stainless 304, powder-coated	Stainless 304, powder-coated
Insulation		Polyurethane, 100 mm	Polyurethane, 70 mm
Weight (blank)	kg	95	120
Spiral(s) for solar collector/hot water	m	10 + 20 + 20	15 + 20 + 20
Capacity coils, kW total	kW	16,30	17,90
R50-Muffe for El-heater		1	2
Electric heater	kW	3	3
Connections Tank/spirals		1 " Inv. Ghost	1 " Inv. Ghost